



CV600

Capturing Every Life Moment





3 ways to make Your shoot more EFFICIENT!



Light Palette

CC/LB Filter library.




FUJIFILM



Present CCT value
Measure by CV600

3



1

Target the amount of CCT


4

Filter recommends

Make presnet CCT value close to Target CCT value.


Choose the filter brand

2



Exposure Value Compensating

Make sure every shoot are always correctly exposed.



EV -2

EV -1

EV 0

EV +1

EV +2

Perfect Shoot

Catch the frequency of light is the key to create a flicker free shoot!



Without Flicker-free Technology



With Flicker-free Technology

Fast Specification

Spectral Bandwidth	Approx 12 nm (half bandwidth)
Wavelength Range	380~780nm
Integration Time Range	6~1000ms
Flicker sampling rate	100 K/sec
Display	3.5"LCD 320x240 Touch Panel
Data Output Interface	SD card/ USB 2.0
Data Format	Compatible Excel / JPG Data Format
Dimensions	144.2x78x24 mm (HxWxD)
Languages	English / Trad. Chinese / Simp. Chinese /Japanese Spanish / German / French / Italian / Russian


The company reserves the right to change product specifications, if it has any changes will not give any notice.

Copyright © United Power Research Technology Corporation. All Rights Reserved.

United Power Research Technology Corporation

+886-37-580-885 +886-37-580-398 www.uprtek.com sales@uprtek.com

No. 38, Keyih St., Chunan, Miaoli County, Taiwan



UPRtek